

## Technical Specifications

Parameters	Value
Motor RPM	1400
Cooling Area*	75 sq.mt / 750 sq.ft
Air throw Distance*	17 mt. / 55 ft.
Air delivery	5100 m <sup>3</sup> .hr / 3000 cfm
<b>Electrical*</b>	
<u>230V / 50-60 Hz</u>	
Wattage	175 W
Max. Current	0.90 amp
<u>110V / 60Hz</u>	
Wattage	200 W
Max. Current	2.14 amp
Blower / Fan	Fan
Fan Diameter	457 mm / 18 inch
Speed Control	Three
Water tank capacity	51 ltr / 14 gallons (US)
Portability	Castors
Vertical louvre movement	Automatic
Float Valve / Ball Cock	Yes
Ice Chamber	Yes
Dust filter net	Yes
Water Level Indicator	Yes
Cooling Media	Aspen
<b>Dimensions (Product)</b>	
Length	647 mm / 25 inch
Breadth	475 mm / 19 inch
Height	1040 mm / 41 inch
<b>Dimensions (Carton)</b>	
Length	707 mm / 28 inch
Breadth	526 mm / 21 inch
Height	1100 mm / 43 inch
<b>Weight</b>	
Product	17 kg / 37 lbs
Incl. Packaging	21 kg / 46 lbs
Certifications	CE, SASO
No.of units per 40 ft container (HC)	132

\* Under test conditions, actual may vary depending on the ambient conditions and the heat load. All specifications are approximate and may vary within  $\pm 10\%$  of the specified value. All products are subject to continuous improvement. The company reserves the right to change specifications without any prior notice.



Seal of Conformity with European directives



Saudi Arabian Standards Organisation




www.symphonycomfort.com  
e-mail: international@symphonycomfort.com

## Portable Evaporative Air Cooler

# winter

Cools upto 75 sq.mt. / 750 sq.ft.\*



Air coolers with Lowest Power Consumption

